

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
30 June 2005 (30.06.2005)

PCT

(10) International Publication Number  
**WO 2005/059372 A1**

(51) International Patent Classification<sup>7</sup>: **F15B 11/024**,  
21/14

(74) Agents: **LUCAS, Laurent** et al.; Thales Intellectual Prop-  
erty, 31-33, Avenue Aristide Briand, F-94117 Arcueil (FR).

(21) International Application Number:  
PCT/EP2004/053526

(81) Designated States (*unless otherwise indicated, for every  
kind of national protection available*): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(22) International Filing Date:  
16 December 2004 (16.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0329243.0 17 December 2003 (17.12.2003) GB

(84) Designated States (*unless otherwise indicated, for every  
kind of regional protection available*): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,  
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,  
GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): **THALES  
UK PLC** [GB/GB]; 2 Dashwood Lang Road, The Bourne  
Business Park, Addlestone near Weybridge, Surrey  
KT152NX (GB).

(72) Inventor; and


(75) Inventor/Applicant (*for US only*): **GROSSART, Stuart,  
James, Cameron** [GB/FR]; Thales Intellectual Property,  
31-33, Avenue Aristide Briand, F-94117 Arcueil (FR).

Published:

— with international search report

[Continued on next page]

(54) Title: APPARATUS AND METHODS FOR ACTUATION



(57) Abstract: There is disclosed an actuator (5) having an actuator chamber (6) and actuator piston (9) therein defining an extend chamber (10) and a retract chamber (7) separated from the extend chamber by the actuator piston. A first fluid pump (A) is in fluid communication with the extend chamber and the retract chamber and is arranged to transfer therebetween volumes of fluid substantially equal in magnitude to changes in the volume of the retract chamber resulting from movement of the actuator piston within the actuator chamber. A second pump B connected to the extend chamber and to an accumulator (17) allows the differential volume between the extend and retract chambers to be displaced into the accumulator at a pressure. Stored accumulator fluid pressure enables pump B to be back-driven so that it behaves as a motor whenever the pressure in conduit 15 is less than in conduit 16. A pre-charge (20) unit pressurises the system until full mass counterbalance of the suspended load is achieved. In this state little or no input power from the servo motor (via pumps A & B) will be needed and significant energy savings can be made.



---

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*